


Features

- 3225 size miniature and light SMD crystal resonator with a low profile of 0.70mm.
- Wide frequency range form a comparatively low 10MHz up to 64MHz.
- High precision and high frequency stability.
- Excellent heat resistance and environmental characteristics.
- Automatic mounting and reflow soldering.
- Applications in PDA, DSC, DVC, Wireless communication, Mobile phone, PC, and more.
- RoHS Compliant / Pb-Free.



Electrical Specifications

Item /Type	7U (3225 SMD crystal resonator)
Frequency Range	10~64MHz
Frequency Tolerance(at 25 °C)	±10ppm~±30ppm, or specify
Frequency Stability Over Operating Temperature Range	±10ppm~±30ppm, or specify
Operating Temperature Range	-40~+85°C, or specify
Shunt Capacitance(C ₀)	3pF Max.
Drive Level	1~200µW Max.(100µW Typical)
Load Capacitance	8pF, 10pF, 12pF, or specify
Aging (at 25°C)	±3ppm / year Max.
Storage Temperature Range	-55~+125°C
Packing Unit	3000pcs./Reel

Equivalent Series Resistance(ESR)

Fundamental	
10~16MHz	100 Ω Max.
16~20MHz	80 Ω Max.
20~64MHz	60 Ω Max.

Dimensions

Units:mm

