




SEP ELECTRONIC CORP.

HER151 thru HER158



1.5 A High Efficiency Rectifier Rectifier Reverse Voltage 50 to 1000V

DO-15



Features

- Diffused junction
- Fast switching for high efficiency
- High current capability and low Forward Voltage Drop
- Surge overload rating to 50A peak
- Low reverse leakage current
- Plastic material has UL flammability classification 94V-0

Mechanical Data

Case: Molded plastic

Terminals: Solder plated solderable per MIL-STD-202,
Method 208

Polarity: Cathode band

Mounting Position: Any

Weight: 0.4 grams (approx)

All dimensions inches and (millimeters)

Maximum Ratings & Thermal Characteristics

Rating at 25°C ambient temperature unless otherwise specified, Resistive or Inductive load, 60 Hz.
For Capacitive load derate current by 20%.

Parameter	Symbol	HER 151	HER 152	HER 153	HER 154	HER 155	HER 156	HER 157	HER 158	unit
Maximum repetitive peak reverse voltage	VRRM	50	100	200	300	400	600	800	1000	V
Maximum RMS bridge input voltage	VRMS	35	70	140	210	280	420	560	700	V
Maximum DC blocking voltage	VDC	50	100	200	300	400	600	800	1000	V
Maximum average forward rectified output current at TA=55°C	IF(AV)					1.5				A
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	IFSM					50				A
Maximum reverse recovery time TJ=25°C	Trr			50			75			nS
Typical thermal resistance per element	ReJA			40						°C/W
Typical junction capacitance per element	C _j		30			20				pF
Operating junction and storage temperature range	T _j , T _{STG}			55 to + 150						°C

Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified. Resistive or Inductive load, 60Hz.
For Capacitive load derate by 20 %.

Parameter	Symbol	HER 151	HER 152	HER 153	HER 154	HER 155	HER 156	HER 157	HER 158	Unit
Maximum instantaneous forward voltage drop per leg at 1.5A	VF		1.0		1.3		1.85			V
Maximum DC reverse current at rated TA =25°C DC blocking voltage per element TA =125°C	IR				10		100			μA

Rating and Characteristic Curves ($T_A = 25^\circ\text{C}$ Unless otherwise noted)
HER151 thru HER158

Fig. 1 Reverse Recovery Time and Test Circuit Diagram




Fig. 2 Derating Curve for Output Rectified Current




Fig. 4 Typical Instantaneous Forward Characteristics




Fig. 3 Peak Forward Surge Current




Fig. 5 Typical Junction Capacitance

